


Recommended Dimmers

DIMMING - DMX

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT PROTOCOL	MAX UNIVER
DMX Controller	TVOQ-1-WH	Indoor	5V DC	DMX 512	1
	TVOQ-2-BK		6V DC		
	TVOQ-2-WH		6-7V DC		
	TVOQ-10-BK-7				
	TVOQ-10-WH-7				



TVOQ-1-WH
WH (White only)



TVOQ-10-XX-7
XX = BK (Black), WH (White)




TVOQ-2-XX
XX = BK (Black), WH (White)


Ordering Information

PRODUCT CODE	LED TYPE	LENS	COLOR TYPE	CONNECTOR	LENGTH
CLL	LB				
Covelum™	LB = LiteBar	C = Clear F = Frosted	22 = 20K 25 = 24K 27 = 27K 30 = 3000K 35 = 3500K 40 = 4000K RD = Red OR = Orange RB = Royal Blue GN = Green BR = Burgundy PP = Purple LG = Leaf Green TG = Teal Green SB = Soft Blue CS = Custom (Consult Factory)	MD = Male/Dead End MF = Male/Female	1 = 1' 2 = 2' 4 = 4' 6 = 6' 8 = 8'

Wiring Accessories



- FEMALE LEAD WIRE**
- CLL-LB-F-LW-1**
1' Lead Wire
- CLL-LB-F-LW-8**
8' Lead Wire
- CLL-LB-F-LW-16**
16' Lead Wire
- CLL-LB-F-LW-25**
25' Lead Wire
- CLL-LB-F-LW-40**
40' Lead Wire



- FEMALE/MALE CONNECTORS**
- CLL-LB-FM-2**
2' Female/Male connector
- CLL-LB-FM-6**
6' Female/Male connector

Factory Service

Covelum™ Outdoor is a sealed unit and must be serviced by factory.

CLL-LB-SERV
In-house service charge (per fixture).