


Ordering Information


PRODUCT CODE	LED COLOR	LED TYPE	LENS TYPE	LENGTH	END PREP**	VOLTAGE
CTL						24
CTL = Continulum™ Indoor	24 = 2400K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	S = Standard U = Ultra Bright	C = Clear F = Frosted O = Opal	1 = 1' 2 = 2' 4 = 4' 6 = 6' 8 = 8'	MD = Male/Dead End MF = Male/Female **Static Lead Wire also required (See below).	24 = 24V DC

Wiring Accessories

**Lead Preparation - Factory attached end preps required. End preps must be indicated at time of ordering.



***LEAD WIRE (Required)**
CTL-LEAD-I-2-F-01
 2 conductor static 1' lead wire.
 Features 24AWG wire on input end
 and 2 pin static female connection
 on other end.
CTL-LEAD-I-2-F-16
 2 conductor static 16' lead wire.
 Features 24AWG wire on input end
 and 2 pin static female connection
 on other end.



MALE/FEMALE JUMPER WIRE
CONN-I-2-01
 Conductor, Jumper 1' Male/Female
CTL-CONN-I-2-16
 Conductor, Jumper 16' Male/Female

Discontinuing