



Features

- Source Voltage
- Input voltage: 120V AC
- Single 12V or 24V DC output
- NEMA 3R Rain-tight enclosure for wet locations
- 5 year warranty
- Dimmable with ELV, MLV, CL forward phase or reverse phase.

Environmental

- MTBF: 100,000 hrs. at full load and 25°C
- Operating temperature: -40°C - +50°C (Full load)
- Storage temperature: -65°C - +90°C
- Heat dissipation: Convection

Mechanical Specification

- Black powdercoated steel enclosure
- Wiring compartment has 2 knock out sizes for 3/8" screw cable connectors

Electrical Data

- Secondary circuit maximum protection for Class 2 circuits: 5A for 12V DC and 1A for 24V DC
- Auto overload protection provided

Ordering Information



DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKER	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY	DIMENSION		
	EMML51412	INDOOR / OUTDOOR	120V AC	12V DC	1	5W	2W	0.4A	2.11"W x 7"L x 1.54"D		
	EMML101812							5W	0.83A	2.11"W x 7"L x 1.54"D	
	EMML2011712							20W	10W	1.67A	2.11"W x 7"L x 1.54"D
	EMML3512912							35W	17W	2.92A	2.11"W x 7"L x 1.54"D
	EMML601512B					60W	30W	5A	2.11"W x 7"L x 1.54"D		
	EMMLH3512912			277V AC	12V DC	1	35W	17W	2.92A	2.11"W x 7"L x 1.54"D	
	EMMLH601512B							60W	30W	5A	2.11"W x 7"L x 1.54"D
	EMML51224		INDOOR / OUTDOOR			120V AC	24V DC	1	5W	2W	0.21A
	EMML101424									10W	5W
	EMML201824							20W	10W	0.83A	2.11"W x 7"L x 1.54"D
	EMML4011724							40W	20W	1.67A	2.11"W x 7"L x 1.54"D
	EMML961424					96W	48W	4A	3.93"W x 8.13"L x 1.59"D		
	EMMLH101424			277V AC	24V DC	1	10W	5W	0.42A	2.11"W x 7"L x 1.54"D	
	EMMLH201824							20W	10W	0.83A	2.11"W x 7"L x 1.54"D
	EMMLH4011724							40W	20W	1.67A	2.11"W x 7"L x 1.54"D
	EMMLH961424						96W	48W	4A	3.93"W x 8.13"L x 1.59"D	

