

24V DC

7.2 W/ft | 729lm/ft

Cuttable 4"

13' Max Continuous Run

Dimmable

VHB Tape

IP54

eXo shield
ultimate dust and moisture protection

90+ CRI

5YR Warranty

RoHS COMPLIANT

c UL us LISTED

2700K 3000K 3500K 4000K 6500K

Ordering Information

PRODUCT CODE		INTENSITY		INSTALL		LED COLOR		VOLTAGE
TPLD	-	VHO	-	I	-		-	24

TPLD Tivotape DEFINE 90+ CRI

VHO Very High Output

I Indoor

27 2700K
30 3000K
35 3500K
40 4000K
65 6500K

24 24V DC

TivoTape Run Lengths & End Preps
Please specify length of run with quantity of run(s) and end prep type at time of ordering.
Note: Only (1) end prep needed for each run (see page 2)

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © Tivoli 11/27/19

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Electrical & Photometric Data (Based on 90+ CRI / 3000K)	
Input Voltage	**24V DC**
Dimming Option	**MLV/ELV/0-10V** *Consult factory for DMX dimming*
Power Supply	**Class 2**
Wire Size (End Prep)	**18 AWG, 2 wire**
Power Consumption	**7.2 W/ft.**
Color Temperature (CCT)	**3000K**
Lumen Output	**668**
Efficacy	**91**
Color Rendering Index (CRI)	**93**
R9	**>50**

Physical	
LED Package	**5630**
Cut Increments	**4”**
LEDs/ft	**18**
Operating Temperature	**-40°F (-40°C) ~ 140°F (60°C)**
Environment	**IP54 Damp Location, Conformal Coated**
Maximum Run Length	**13’**
Copper Trace	**3 Ounce**
Adhesive	**3M VHB Tape**
Dimension	**13/32” (10mm)**

Performance	
Certification	**UL Listed**
Lumen Maintenance (L70) Hours	**60,000**
Binning Tolerance	**2 Step MacAdam Elipse**
Warranty	**5 Years**

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © Tivoli 11/27/19

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Power Leads and Jumpers (Installed by Tivoli's certified solderers)



TPL-I-LEAD-C
LEAD END
24" standard 2 conductor 18AWG lead wire factory attached to one end of tape.



TPL-I-LEAD-D
LEAD/LEAD
24" standard 2 conductor 18AWG lead wire factory attached to both ends of tape.



TPL-I-XEP
EXTRA LEAD WIRE
Additional factory attached 18AWG lead wire to extend lengths of LEAD-C and LEAD-D up to 20 ft max. Sold per foot (not shipped as spooled wire).



TPL-I-CONN
18-22AWG BUTT CONNECTORS
Used to interconnect factory attached lead wires. Sold individually.
(2 ea required per connection).

Mounting Channel

M CHAN





MCHAN-8-LP
Low profile mounting channel, clear polycarbonate, length 8'.

NOTE: No Lens option

M CHAN 45



TPL-I-45-MCH-8-S
45˚ Mounting channel, NO LENS OPTION white PVC, length 8'.

INFINITY CHANNEL





INF-C-CHAN-8
Channel & lens, clear length 8'.

INF-F-CHAN-8
Channel & lens, frosted length 8'.

INF-EC
End Cap, Black

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © Tivoli 11/27/19

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

MOSHER



MOSR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

MOSR-LNS-OP-6.5
Lens, opal, length 6.5′

MOSR-EC-01
Solid End Cap

MOSR-EC-02
Powerfeed End Cap

MTBK-03
Mounting Clip

DYER





DYER-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

DYER-LNS-OP-6.5
Lens, opal, length 6.5′

DYER-EC-01
Solid End Cap

DYER-EC-02
Powerfeed End Cap



DYER-MTBK
Mounting Clip

VALENCIA





VALN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

VALN-LNS-OP-6.5
Lens, opal, length 6.5′

VALN-EC-01
Solid End Cap

VALN-EC-02
Powerfeed End Cap

VALN-MTBK
Mounting Clip

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

MINI







MINI-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

MINI-LNS-OP-6.5
Lens, opal, length 6.5′



MINI-EC-01
Solid End Cap

MINI-EC-02
Powerfeed End Cap

MINI-MTBK
Mounting Clip

MINI-ADJ-MTBK
Adjustable Mounting Clip

WARNER







WRNR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

WRNR-LNS-OP-6.5
Lens, opal, length 6.5′

WRNR-EC-01
Solid End Cap

WRNR-EC-02
Power feed End Cap



WRNR-MTBK
Mounting Clip

EDINGER







EDIN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

EDIN-LNS-OP-6.5
Lens, opal, length 6.5′



EDIN-EC-01
Solid End Cap

EDIN-EC-02
Powerfeed End Cap

MTBK-03
Mounting Clip

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

HORIZON







HRIZ-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

HRIZ-LNS-OP-6.5
Lens, opal, length 6.5′

HRIZ-EC-01
Solid End Cap

HRIZ-EC-02
Powerfeed End Cap

NOVA





NOVA-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

NOVA-LNS-OP-6.5
Lens, opal, length 6.5′

NOVA-EC-01
Solid End Cap

NOVA-EC-02
Powerfeed End Cap

MTBK-03
Mounting Clip

DOME



DOME-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

DOME-LNS-OP-6.5
Lens, opal, length 6.5′

DOME-EC-01
Solid End Cap

DOME-EC-02
Powerfeed End Cap

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

ALTON







ALTN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

ALTN-LNS-OPL-6.5
Lens, opal, length 6.5′

ALTN-LNS-CLR-6.5
Lens, clear, length 6.5′

ALTN-LNS-DIF-6.5
Lens, diffuser, length 6.5′

ALTN-EC-01
Solid End Cap

ALTN-EC-02
Powerfeed End Cap

NOYES







NOYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

NOYS-LNS-OPL-6.5
Lens, opal, length 6.5′

NOYS-LNS-CLR-6.5
Lens, clear, length 6.5′

NOYS-LNS-DIF-6.5
Lens, diffuser, length 6.5′

NOYS-EC-01
Solid End Cap

NOYS-EC-02
Powerfeed End Cap

NOYS-SPRiNG-CLP
Clip, Spring, Metal

MARSALA







MRSL-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

MRSL-LNS-OPL-6.5
Lens, opal, length 6.5′

MRSL-LNS-CLR-6.5
Lens, clear, length 6.5′

MRSL-LNS-DIF-6.5
Lens, diffuser, length 6.5′

MRSL-EC-01
Solid End Cap

MRSL-EC-02
Powerfeed End Cap

MRSL-CLP-SLV
Clip, Metal

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

DEWAR





DWAR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

DWAR-LNS-OPL-6.5
Lens, opal, length 6.5′

DWAR-LNS-CLR-6.5
Lens, clear, length 6.5′

DWAR-LNS-DIF-6.5
Lens, diffuser, length 6.5′

DWAR-EC-01
Solid End Cap

DWAR-EC-02
Powerfeed End Cap

DWAR-CLP-SLV
Clip, Metal

ASTORIA





ASTR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

ASTR-LNS-DIF-6.5
Lens, diffuser, length 6.5′

ASTR-LNS-CLR-6.5
Lens, clear, length 6.5′

ASTR-EC-01
Solid End Cap

ASTR-EC-02
Powerfeed End Cap



ASTR-CLP-SLV
Clip, Metal

MOFETT



MOFT-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

MOFT-LNS-OPL-6.5
Lens, opal, length 6.5′

MOFT-LNS-CLR-6.5
Lens, clear, length 6.5′

MOFT-LNS-DIF-6.5
Lens, diffuser, length 6.5′

MOFT-EC-01
Solid End Cap

MOFT-EC-02
Powerfeed End Cap



MOFT-CLP-SLV
Clip, Metal

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

EDGE





EDGE-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

EDGE-LNS-OP-6.5
Lens, opal, length 6.5′

EDGE-EC-01
Solid End Cap

EDGE-EC-02
Powerfeed End Cap

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Recommended Power Supplies

ADUL - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-120-1-4-24-D	Indoor / Damp	100-277V AC 50/60 HZ	24V DC	1	96W	4A
	ADUL-240-2-4-24-D				2	2x96W	2x4A
	ADUL-320-3-4-24-D				3	3x96W	3x4A

ADUL - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-120-1-4-24-DOT	Indoor / Damp	100-277V AC 50/60 HZ	24V DC	1	96W	4A
	ADUL-240-2-4-24-DOT				2	2x96W	2x4A
	ADUL-320-3-4-24-DOT				3	3x96W	3x4A

ADUL - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-120-1-4-24-DIN	Indoor / Damp	100-277V AC 50/60 Hz	24V DC	1	96W	4A
	ADUL-240-2-4-24-DIN				2	2x96W	2x4A
	ADUL-320-3-4-24-DIN				3	3x96W	3x4A

ADUL - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-240-2-4-24-DIN-2	Indoor / Damp	100-277V AC 50/60 Hz	24V DC	2	2x96W	2x4A
	ADUL-320-3-4-24-DIN-3				3	3x96W	3x4A

ADNM - DMX/DALI FLICKER-FREE FOR TV STUDIO

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-120-1-4-24-DTV	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	1	1x96W	1x4A
	ADNM-240-2-4-24-DTV				2	2x96W	2x4A
	ADNM-320-3-4-24-DTV				3	3x96W	3x4A

INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-1.3-24	Indoor / Outdoor	100 - 277V AC	24VDC	1	30W	3W	1.3A
	INF-J-60-1-2.5-24				1	60W	6W	2.5A
	INF-J-96-1-4-24				1	96W	9W	4A
	INF-J-192-2-4-24				2	2x96W	2x9W	2x4A
	INF-J-288-3-4-24				3	3x96W	3X9W	3x4A

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Recommended Dimmers

DIMMING - 0-10V

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
0-10V Dimmer	DIM-LD-010	Indoor	12V/24V DC	12V/24V DC	30 mA max. output (sink only)

DIMMING - MLV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
MLV Dimmer	N-600	Indoor	120V AC	120V AC	450W
	N-1000				800W
	N-1500				1200W
	D-600				450W
	M-600				450W
	M-1000				800W

DIMMING - ELV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
ELV Dimmer	ME-600	Indoor	120V AC	120V AC	450W
	DE-300				300W

DIMMING - DMX

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT PROTOCOL	MAX UNIVERSE
DMX Controller	TVOQ-1-WH	Indoor	5V DC	DMX 512	1
	TVOQ-2-BK		6V DC		
	TVOQ-2-WH				
	TVOQ-10-BK-7		6-7V DC		
	TVOQ-10-WH-7				2

Touchscreen

TVOQ-1-WH
WH (White only)



Touchscreen

TVOQ-10-XX-7
XX = BK (Black), WH (White)

Touchscreen

TVOQ-2-XX
XX = BK (Black), WH (White)

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.