ELITE

ZERO DROP TECHNOLOGY

Discontinued



HO ELITE TivoTape™

Project: _____ TYPE: _____

- Low bin tolerance with a 1.5 Step McAdam Elipse standard
- Factory produced with Tivoli's eXo Shield coating
- High CRI value
- Factory soldered lead wire
- IP67 Wet location available
- Multiple mounting channel options
- Large range of available Kelvin temperatures
- Low lead times
- 4oz. Copper Trace
- 5 Year warranty

Dimensions

c UL us LISTED



Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Order Guide

PRODUCT CODE		INTENSITY		INSTALL		LED COLOR		LENGTH		VOLTAGE
TPLE	-	HO	-	I	-		-		-	24
TPLE = TivoTape ELITE		**HO** = High Output		**I** = Indoor		**22** = 2200K **24** = 2400K **27** = 2700K **40** = 4000K **50** = 5000K		**R** = * Full Roll (164 ft) **MR** = Maximum Run (21')		= 24V DC

*Leave blank if specifying run lengths. A layout/drawing must accompany each order showing run length and location
Note: A layout/drawing must accompany each order showing run length and location
Note: Runs with LEAD-C are rounded **up** to next cut interval (unless otherwise specified)
Note: Runs with LEAD-D are rounded **down** to next cur interval (unless otherwise specified)
Note: For the full range of CCT options, please refer to the Elite Plus specification

Specification

Output (based on 4000K)					
Kelvin Temperature	2200K	2400K	2700K	4000K	5000K
Lumens/ft	464	[illegible]	513	549	558
Efficacy (Lm/W)	103	108	114	122	124
Color Rendering Index (CRI)	90+				
Electrical					
Input Voltage	2[illegible]				
Power Supply	Cl[illegible]2				
Power Consumption W/ft	4.5 W/ft.				
Maximum Run Length	20'				
Maximum Run Length w/ JA8	17'				
Wire Size (End Prep)	[illegible] AWG, 2 wire				
Dimming	MLV/ELV/0-10V/DMX				
Physical					
LED [illegible]	2835				
Copper Trace	4 Ounce				
Adhesive	3M VHB Tape				
Dimensions	15/32" W (12mm)				
Cut Increments	1 5/16"				
Operating Temperature	-40°F (-40°C) ~ +140°F (+60°C)				
Certification and Testing					
Certification	UL Listed				
Lumen Maintenance (L70) Hours	60,000				
Binning Tolerance	1.5 Step MacAdam Elipse				
IP Rating	IP20				
Environment	IP54 Damp Location, Conformal eXo Shield Coated				
Warranty	5 years				

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Photometrics Based on 4000K



Maximum Candela = 159.26
Located At Horizontal Angle = 0
Vertical Angle = 0
#1 Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
#2 Vertical Cone Through Vertical Angle (0) (Through Max. Cd.)



Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

TM30 Based on 3000K

Rf 92	Rg100
Fidelity index Rf	Gamut index Rg









This plot shows a comparison of the Rf and Rg values relative to the range of possible values .

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Power Leads and Jumpers (Installed by Tivoli's certified solderers)



TPL-I-LEAD-2-C
LEAD/END
24" standard 2 conductor 18AWG lead wire factory attached to one end of tape



TPL-I-LEAD-2-D
LEAD/LEAD
24" standard 2 conductor 18AWG lead wire factory attached to both ends of tape



TPL-I-XEP-2
EXTRA LEAD WIRE
Additional factory attached 18AWG lead 2 wire to extend lengths of LEAD-C and LEAD-D up to 20 ft. max
Sold per foot



TPL-I-C NN
18-22A G BU CO NECTORS
Used in conne actory
ttache ad wi
S individu

Snap Power Lead and Jumpers (For in-field connecti n)

TPL-I-12-SNP-LEAD-XX
XX = **12** (12"), **60** (60")
2 conductor 20AWG lead wire field attached
Sold 10pcs

TPL-I-12-SNP-JUMPER-6
6" 2 conductor mper
wire field att ed
Sold 10pcs

TPL-I-12-SNP-JOINER
2 conductor joiner field ttached
Sold 10pcs



Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © Tivoli 09/22/26

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Compatible Extrusions

Fits 12mm Snap Connector



MCHAN-8-LP
Low profile NO LENS OPTION clear polycarbonate, length 8′



TPL-I-45-MCH-8-S
White PVC, 45° NO LENS length 8′



DWAR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



E GE-CHA SLV-6.5
A odize Alum m Extrusion, a ilable in 6. engths



MINI-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



MOFT-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths

EDA-C N-SLV-6.
nodized minum Extrusion, ilable in 6. lengths



WRNR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



NOYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



NZI-CHA XX-6.
XXX=SLV (Silver), **BLK** (Black), **WHT** (White)
Anodized uminum Extrusion, ilab n 6.5′ lengths



DOME-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



ALTN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



M -CHAN V-6.5
Anod minum extrusion availab n 6.5′ length



HRIZ-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



ASTR-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



INF-X-CHAN-8
X = **C** (clear), **F** (frosted) PC extrusion, available in 8′ lengths

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Compatible Extrusions

Fits 12mm Snap Connector



COTA-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



CARU-CHAN-SLV-6.5
Anodized aluminum extrusion, available in 6.5′ lengths



HAYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



DUF 04-CHA XXX-6.5
XX = **SLV** (Silver), **WHT** (white), **GLL**, **BLK** (Black)
Alumi extru
Length



DUET-04-CHAN-M-6.5
Mud-In PC fire-proof extrusion 6.5′ Length

Note: **DUET-04-CHAN-SLV-6.5** and **DUET-04-CHAN-M-6.5** are required for mud-in application



DUET-04-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length

Note: **DUET-04-CHAN-SLV-6.5** and **DUET-04-LNS-R-XXX-6.5** are required for recessed application



FR -CHA LV-6.5
odized Al num Extrusion, av ble in 6.5 ngths



RIDG-CHAN-SLV-8
Anodized Aluminum Extrusion length 8′

Note: For complete information on DUET 04 profile, refer to spe ication

In-Wall Controls

Touch reen

VOQ-1-WH
White

Touchscreen

TVOQ-10-XX-7
XX = **BK** (Black), **WH** (White)

Touchscreen

TVOQ-2-BK
Black

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Power Supplies

INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-1.3-24	Indoor / Outdoor	100 - 277V AC	24V DC	1	30W	3W	1.3A
	INF-J-60-1-2.5-24				1	60W	6W	2.5A
	INF-J-96-1-4-24				1	96W	9W	4A
	INF-J-192-2-4-24				2	2x96W	18W	2x4A
	INF-J-288-3-4-24				3	3x96W	3X9W	3x4A

ER

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ER Series Class 2 Driver	ER-80-1-3.3-24-D	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	1	80W	3.3A
ER Series Class 2 0-10V Dimming	ERG-80-24-DIM1-10						

ADUL/ADNM - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL/ADNM Series Class 2 Transformer	ADNM-90-1-4-24-D	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADUL-120-1-4-24-D				1	96W	4A
	ADUL-240-2-4-24-D	Indoor			2	2x96W	2x4A
	ADUL-320-3-4-24-D	Indoor			3	3x96W	3x4A

ADUL/ADNM - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL/ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DOT	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADUL-120-1-4-24-DOT	Indoor			1	96W	4A
	ADUL-240-2-4-24-DOT	Indoor			2	2x96W	2x4A
	ADUL-320-3-4-24-DOT	Indoor			3	3x96W	3x4A

ADUL/ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL/ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DIN	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	1	90W	3.75A
	ADUL-120-1-4-24-DIN	Indoor			1	96W	4A
	ADUL-240-2-4-24-DIN	Indoor			2	2x96W	2x4A
	ADUL-320-3-4-24-DIN	Indoor			3	3x96W	3x4A

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Power Supplies

ADUL - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-240-2-4-24-DIN-2	Indoor	100-277V AC 5o/60 Hz	24V DC	2	2x96W	2x4A
	ADUL-320-3-4-24-DIN-3				3		

ADNM - DMX/DALI FLICKER-FREE FOR TV STUDIO

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-120-1-4-24-DTV	Indoor / Outdoor	100-277V AC 50/60 HZ	24V	1	1x96W	1x4A
	ADNM-240-2-4-24-DTV				2	2x96W	2x4A
	ADNM-320-3-4-24-DTV				3	3x96W	3x4A

Dimmers

DIMMING - 0-10V

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
0-10V Dimmer	DIM-LD-010	Indoor	12V/24V DC	12V/24V DC	30 mA max. output (sink only)

DIMMING -MLV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
MLV Dimmer	N-600	Indoor	120V AC	120V AC	450W
	N-1000				800W
	N-1500				1200W
	D-600				450W
	M-600				450W
	M-1000				800W

DIMMING - ELV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
ELV Dimmer	ME-600	Indoor	120V AC	120V AC	450W
	DE-300				300W

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.