ELITE

ZERO DROP TECHNOLOGY

Discontinued



SB Outdoor ELITE TivoTape™

Project: _____ TYPE: _____

- Low bin tolerance with a 1.5 Step McAdam Elipse standard
- 4oz. Copper trace produces no lumen drop at end of max run
- Outdoor location suited with Tivoli's eXo Shield coating
- High CRI value
- Factory soldered lead wire installed
- IP67 Wet location available
- Multiple mounting channel options
- Large range of available Kelvin temperatures
- Low lead times
- 3 Year warranty

Dimensions

c UL us LISTED

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 09.23.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Order Guide

PRODUCT CODE		INTENSITY		INSTALL		LED COLOR		VOLTAGE
TPLE	-	**SB**	-	**O**	-		-	**24**
TPLE = TivoTape ELITE		**SB** = Standard Brightness		**O** = Outdoor		**22** = 2200K **40** = 4000K **50** = 5000K		24 = 24V DC

Note: A layout/drawing must accompany each order showing run length and location
Note: Runs with LEAD-C are rounded **up** to next cut interval (unless otherwise specified)
Note: Runs with LEAD-D are rounded **down** to next cut interval (unless otherwise specified)
Note: For the full range of CCT options, please refer to the Elite Plus specification

Specification

Output (based on 3000K)							
Kelvin Temperature	2200K	[illegible]K	270[illegible]	3000K	3500K	4000K	5000K
Lumens/ft	291	307	323	328	332	346	350
Efficacy (Lm/W)	91	[illegible]7	[illegible]7	97	94	93	90
Color Rendering Index (CRI)	90+						
Electrical							
Input Voltage	24						
Power Supply	Cl[illegible]2						
Power Consumption W/ft	3.2 W[illegible]						
Maximum Run Length	29'						
Maximum Run Length (JA8)	24'						
Wire Size (End Prep)	1[illegible]VG, 2 wire						
Dimming	MLV/ELV/0-10V/DMX						
Physical							
LED Package	2835						
[illegible]s/ft	73						
Adhesive	3M VHB Tape						
Copper Trace	4 Ounce						
[illegible]ensions	19/32" (15mm)						
Cu[illegible]ements	1 5/16"						
Operat[illegible] T[illegible]perature	-40°F (-40°C) ~ +140°F (+60°C)						
Certificatio[illegible] and Testing							
Certification	UL Listed						
Lumen Maintenance (L70) Hours	60,000						
Binning Tolerance	1.5 Step MacAdam Elipse						
Environment	IP67 Wet Location						
Warranty	3 years						

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.



Maximum Candela = 110.4
Located At Horizontal Angle = 0
Vertical Angle = 2.5
#1 Vertical Plane Through Horizontal Angles (0-180) (Through Max. Ca.
#2 Vertical Cone Through Vertical Angle (0) (Through Max. Cd.)



Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

TM-30



Color Vector Graph

Color Distortion Graphic



Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

TM-30





Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Power Leads and Jumpers (Installed by Tivoli's certified solderers)



TPL-O-LEAD-2-C
LEAD/END
24" standard 2 conductor 18AWG lead wire factory attached to one end of tape



TPL-O-LEAD-2-D
LEAD/LEAD
24" standard 2 conductor 18AWG lead wire factory attached to both ends of tape



TPL-O-XEP-2
EXTRA LEAD WIRE
Additional factory attached 18AWG lead 2 wire to extend lengths of LEAD-C and LEAD-
up to 20 ft. max
Sold per foot



TP
22AWG UTT CONNECTORS
ed t nterco nect factory
ed lead ires.
So ivid ly.

GELJB-3-01-BK
1/2/3 Wire IP67 Small Gel Filled Junction Box

GELJB-3-02-BK
1/2/3 Wire IP67 Medium Gel Filled Junction Box

In-Wall Controls

TVOQ-1-WH
W

VOQ-10-XX-7
XX = **BK** (Black), **WH** (White)

TVOQ-2-BK
Black

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Compatible Extrusions



MOFT-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



WRNR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



NOYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



FRE HAN-SL 6.5
An lized A min Extrusion, ava ble in 6.5′ ngths



DOME-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



ALTN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



TA-CHA SLV-6.5
dized Alu um Extrusion, ava ble in 6.5 engths



MRSL-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



HRIZ-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Recommended Power Supplies

ADNM - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-D	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-D				1		
	ADNM-240-2-4-24-D				2	2x	2x4A
	ADNM-320-3-4-24-D				3	x96W	3x4A

ADNM - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DOT	Indoor / Outdoor	100 V AC 50/ HZ	24V DC		90W	3.75A
	ADNM-120-1-4-24-DOT				1	96W	4A
	ADNM-240-2-4-24-DOT				2	2x96W	2x4A
	ADNM-320-3-4-24-DOT				3	3x96W	3x4A

ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DIN	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-DIN				1	96W	4A
	ADNM-240-2-4-24-D				2	2x96W	2x4A
	ADNM-320-3-4-24				3	3x96W	3x4A

ADNM - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
A Series Class 2 Transformer	ADNM-240-2-4-24-DIN-2	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	2	2x96W	2x4A
	ADN 20-3-4-24-DIN-3				3	3x96W	3x4A

ADNM - DM DALI FL KER-FREE FOR TV STUDIO

DESCRIPT N	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
D Series C Transformer	ADNM-120-1-4-24-DTV	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	1x96W	1x4A
	ADNM-240-2-4-24-DTV				2	2x96W	2x4A
	ADNM-320-3-4-24-DTV				3	3x96W	3x4A

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Recommended Power Supplies

INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-1.3-24	Indoor / Outdoor	100 - 277V AC	24V DC	1	30W	3W	1.3A
	INF-J-60-1-2.5-24				1	60W		
	INF-J-96-1-4-24				1	96W	9W	4A
	INF-J-192-2-4-24				2	2x96W	2	2x4A
	INF-J-288-3-4-24				3	3x96	X9W	3x4A

ER - JA8 W/ELITE 3000K

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECO ARY VO GE	CIRCUI REAKERS	MAX LOAD	CIRCUIT CAPACITY
ER Series Class 2	ER-80-1-3.3-24-D	Indoor / Outdoor	100-277V AC 50/60 Hz	24V		80W	3.3A
ER Series Class 2 0-10V Dimming	ERG-80-24-DIM1-10						

Recommended Dimmers

DIMMING - 0-10V

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD	PRICE
0-10V Dimmer	DIM-LD-010	Indoor	12V/24V DC	12V/24V DC	30 mA max. output (sink only)	$ 120.00/ea

DIMMING -MLV

ESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
Dimmer	N-600	Indoor	120V AC	120V AC	450W
	N-1000				800W
	N-1500				1200W
	D-600				450W
	M-600				450W
	M-1000				800W

DIMMING - ELV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
ELV Dimmer	ME-600	Indoor	120V AC	120V AC	450W
	DE-300				300W

Discontinued

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 09.23.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458