Project: _____ Type: _____

- Silcone sleeved for outdoor rating
- Multiple intensities to choose from
- Low bin tolerance with a 1.5 Step McAdam Elipse standard
- High efficacy value
- Includes Tivoli's eXo shield coating
- Factory soldered lead wire
- Standard IP67 wet rated and IP54 damp location available
- Multiple mounting channel options
- Large range of available Kelvin temperatures
- Low lead times
- 4oz. Copper Trace

Dimensions

c UL us LISTED



Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 03.02.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Order Guide

PRODUCT CODE		TYPE		INTENSITY		INSTALL		LED COLOR		VOLTAGE
TPLEP	-	PR	-		-	O	-		-	24
TPLEP = TivoTape ELITE Plus+		**PR** = Pro		**LB** = Low Brightness **SB** = Standard Brightness **HO** = High Output		**O** = Outdoor		**18** = 1800K **22** = 2200K **24** = 2400K **27** = 2700K **30** = 3000K **35** = 3500K **40** = 4000K **50** = 5000K		**24** = 24V

Note: A layout/drawing must accompany each order showing run length and location
Note: Runs with LEAD-C are rounded **up** to next cut interval (unless otherwise specified)
Note: Runs with LEAD-D are rounded **down** to next cur interval (unless otherwise specified)

Specification

LB Low Brightness								
Kelvin Temperature	1800K	2200K	2400K	2700K	3000K	3500K	4000K	5000K
Lumens/ft	CF	CF	61.9	191	CF	CF	CF	CF
Efficacy (Lm/W)	CF	CF	153	159	CF	CF	CF	CF
CRI	CF	CF	CF	CF	CF	CF	CF	CF
Measured Power W/ft	CF	CF	1.2	1.2	CF	CF	CF	CF
Listed Power W/ft.	1.5							
Max Mechanical Run	15′							
Max Electrical Run	64′							

SB Standard Brightness								
Kelvin Temperature	1800K	2200K	2400K	2700K	3000K	3500K	4000K	5000K
Lumens/ft	CF	CF	425	444	455	478	471	CF
Efficacy (Lm/W)	CF	CF	147	154	157	162	180	CF
CRI	CF	CF	92	93	93	94	93	CF
Measured Power W/ft	CF	CF	2.9	2.9	2.9	2.9	2.6	CF
Listed Power W/ft.	3							
Max Mechanical Run	15′							
Max Electrical Run	30′							

HO High Output								
Kelvin Temperature	1800K	2200K	2400K	2700K	3000K	3500K	4000K	5000K
Lumens/ft	CF	CF	CF	506	561	579	584	CF
Efficacy (Lm/W)	CF	CF	CF	160	160	164	176	CF
CRI	CF	CF	CF	93	93	93	93	CF
Measured Power W/ft	CF	CF	CF	3.2	3.5	3.5	3.3	CF
Listed Power W/ft.	4.5							
Max Mechanical Run	15′							
Max Electrical Run	20′							

Electrical	
Input Voltage	24V
Dimming	MLV/ELV/0-10V/DMX
Physical	
LED Package	5630
LEDs/ft	54
Adhesive	3M VHB Tape
Copper Trace	4 Ounce
Dimensions	0.594″ (15mm)
Cut Increments	2″ (50.8mm)
Operating Temperature	-40°F (-40°C) ~ +140°F (+60°C)
Certification and Testing	
Certification	UL Listed, CE
Lumen Maintenance (L70)	60,000 hrs
Binning Tolerance	1.5 Step MacAdam Elipse
Environment	IP54 Damp Location, Conformal eXo Shield
Warranty	5 years

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 03.02.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Power Leads and Jumpers (Installed by Tivoli's certified solderers)



TPL-O-LEAD-2-C
LEAD/END
24" standard 2 conductor 18AWG lead wire factory attached to one end of tape



TPL-O-LEAD-2-D
LEAD/LEAD
24" standard 2 conductor 18AWG lead wire factory attached to both ends of tape



TPL-O-XEP-2
EXTRA LEAD WIRE
Additional factory attached 18AWG lead 2 wire to extend lengths of LEAD-C and LEAD-D up to 20 ft. max
Sold per foot



TPL-O-CONN
18-22AWG BUTT CONNECTORS
Used to interconnect factory attached lead wires.
Sold individually.

GELJB-3-01-BK
1/2/3 Wire IP67 Small Gel Filled Junction Box

GELJB-3-02-BK
1/2/3 Wire IP67 Medium Gel Filled Junction Box

In-Wall Controls

TVOQ-1-WH
White

TVOQ-10-XX-7
XX = **BK** (Black), **WH** (White)

TVOQ-2-BK
Black

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Compatible Extrusions



CARU-CHAN-SLV-6.5
Anodized aluminum extrusion, available in 6.5′ lengths



WRNR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



NOYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



FRE-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



DOME-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



ALTN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



COTA-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



HAYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



HRIZ-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



ANZI-CHAN-XXX-6.5
XXX=SLV (Silver), **BLK** (Black), **WHT** (White)
Anodized Aluminum Extrusion, available in 6.5′ lengths



MOFT-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



MRSL-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Recommended Power Supplies

INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-1.3-24	Indoor / Outdoor	100 - 277V AC	24V DC	1	30W	3W	1.3A
	INF-J-60-1-2.5-24				1	60W	6W	2.5A
	INF-J-96-1-4-24				1	96W	9W	4A
	INF-J-192-2-4-24				2	2x96W	2x9W	2x4A
	INF-J-288-3-4-24				3	3x96W	3X9W	3x4A

ER - JA8 W/ELITE 3000K

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ER Series	ER-80-1-3.3-24-D	Indoor / Outdoor	100-277V AC 5o//60 Hz	24V DC	1	80W	3.3A
ER Series	ERG-80-24-DIM1-10						

ADNM - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-D	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-D				1	96W	4A
	ADNM-240-2-4-24-D				2	2x96W	2x4A
	ADNM-320-3-4-24-D				3	3x96W	3x4A

ADNM - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DOT	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-DOT				1	96W	4A
	ADNM-240-2-4-24-DOT				2	2x96W	2x4A
	ADNM-320-3-4-24-DOT				3	3x96W	3x4A

ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DIN	Indoor / Outdoor	100-277V AC 5o/60 Hz	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-DIN				1	96W	4A
	ADNM-240-2-4-24-DIN				2	2x96W	2x4A
	ADNM-320-3-4-24-DIN				3	3x96W	3x4A

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Recommended Power Supplies

ADNM - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-240-2-4-24-DIN-2	Indoor / Outdoor	100-277V AC 5o//60 Hz	24V DC	2	2x96W	2x4A
	ADNM-320-3-4-24-DIN-3				3	3x96W	3x4A

ADNM - DMX/DALI FLICKER-FREE FOR TV STUDIO

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-120-1-4-24-DTV	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	1x96W	1x4A
	ADNM-240-2-4-24-DTV				2	2x96W	2x4A
	ADNM-320-3-4-24-DTV				3	3x96W	3x4A

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 03.02.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458