


ANZIO

Design Guide



Profile & Dimensions



Available TivoTape Options - Indoor

DEFINE

SB
HO
LB

ELITE

SB
HO
VHO

ELITE+

Plus
Pro
Vision
Flow

FUSE24

RGB
RGB+W
RGB+W+W
DW
Pixle24 RGB
Pixle24 RGBW

FUSE12

PiXEL12 RGB

Available TivoTape Options - Outdoor

DEFINE

SB
HO
LB

FUSE24

RGB

FUSE12

PiXEL12 RGB

Ordering Information



ANZI-CHAN-XXX-6.5

XXX = SLV (Silver)
WHT (White), **BLK** (Black)
ABLK (Anodized Black)
Aluminum Extrusion
available in 6.5' lengths



ANZI-EC-XXX-XX

XXX=WHT (White), **BLK** (Black),
SIL (Silver)
XX = 01 (no power feed),
02 (with power feed)
End cap solid each



ANZI-LNS-SIL-XXX-XXX

XXX= DIF (Diffused), **BLK** (Black)
XXX (unit in feet) = **10, 50, 100**
Silicone lens sold in roll



ANZI-LNS-XXX-6.5

XXX=CLR (Clear), **DIF** (Diffused), **OPL** (Opal)
Lens available in 6.5' lengths



ANZI-SS-CBL
Anzio Urban Stainless Steel
Suspension
Factory standard length 41'