tivoli®

The Original Tivolite LED Filament Bulb

Project: _____ TYPE: _____

- Compatible with 4-way chasing
- Available in 2, 4 and 6 LED filament
- Multiple LED filament - one side goes out, the other(s) stays lit
- Long life span - 30,000 hours
- Glass, PET, and PC vacuum sealed bulb
- Nickel coated brass base to eliminate corrosion due to weather conditions
- Mercury free
- Save 85-90% energy with a direct LED replacement of incandescent lamps
- 360 Degree light distribution
- Excellent heat dissipation

IP65 IP54 ETL LISTED

Dimension



G10



G12



A19



S14 / 4W

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © Tivoli 09/30/26

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Order Guide - Glass

PRODUCT CODE	TYPE	FILAMENT	FINISH	SOCKET	LED COLOR	VOLTAGE
TVLT			**C**	**12**		**120**
TVLT = Tivolite Bulb	**G10** = G10 Bulb **G12** = G12 Bulb	**2** = 2 Filament	**C** = Clear	**12** = E12	**22** = 2200K **24** = ***2400K **27** = 2700K **30** = 3000K	**120** = 120V AC

PRODUCT CODE	TYPE	FILAMENT	FINISH	SOCKET	LED COLOR	VOLTAGE
TVLT				**26**		**120**
TVLT = Tivolite Bulb	**A19** = A19 Bulb **S14** = S14 Bulb	**2** = 2 Filament **4** = 4 Filament **6** = *6 Filament	**F** = **Frosted **V** = Vintage (-15% CCT Shift) **C** = Clear	**26** = E26	**22** = 2200K **24** = ***2400K **27** = 2700K **30** = 3000K	**120** = 120V AC

*Note: Available only in A19 type
**Note: Available only in 4 and 6 filament for A19 & S14 type
***MOQ - Consult Factory

Specification

2 Filament (based on Clear 2200K)	G10	G12	A19	S14
Lumens (lm/fixture)	80	105	105	105
CRI	>80			
Efficacy (lm/W)	80	105	52.5	52.5
Beam Angle	360°			
Power Consumption (W/Bulb)	1W	1W	2W	2W
4 Filament (based on Clear 2700K)	G10	G12	A19	S14
Lumens (lm/fixture)	N/A	N/A	CF	400
CRI	N/A	N/A	CF	>80
Efficacy (lm/W)	N/A	N/A	CF	100
Beam Angle	N/A	N/A	CF	360°
Power Consumption (W/Bulb)	N/A	N/A	4W	4W
6 Filament (based on Clear 3000K)	G10	G12	A19	S14
Lumens (lm/fixture)	N/A	N/A	717.6	N/A
CRI	N/A	N/A	84.8	N/A
Efficacy (lm/W)	N/A	N/A	115.7	N/A
Beam Angle	N/A	N/A	360°	N/A
Power Consumption (W/Bulb)	N/A	N/A	6.2W	N/A
Control	G10	G12	A19	S14
Dimming	NO	YES	YES	YES
Electrical				
Input Voltage	120V AC			
Physical				
Bulb	Vacuum Sealed			
Base	Nickle Coated Brass Base			
Certification and Testing				
Certification	ETL			
Environment (Glass Bulb)	Outdoor Location			
IP Rating	IP65			
Rated Life	30,000 hrs.			
Warranty	5 years			

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Order Guide - PET/PC Indoor Use Only

PRODUCT CODE	TYPE	FILAMENT	FINISH	SOCKET	LED COLOR	VOLTAGE
TVLTPC	**S14**			**26**		**120**
TVLTPC = Tivolite PC Bulb	**S14** = *S14 Bulb	**2** = 2 Filament	**V** = Vintage (-15% CCT Shift) **C** = Clear	**26** = E26	**22** = 2200K **24** = ***2400K **27** = 2700K **30** = 3000K	**120** = 120V AC

PRODUCT CODE	TYPE	FILAMENT	FINISH	SOCKET	LED COLOR	VOLTAGE
TVLTPET	**A19**			**26**		**120**
TVLTPET = Tivolite PET Bulb	**A19** = A19 Bulb	**2** = 2 Filament **4** = 4 Filament	****F** = Frosted **V** = Vintage (-15% CCT Shift) **C** = Clear	**26** = E26	**22** = 2200K **24** = ***2400K **27** = 2700K **30** = 3000K	**120** = 120V AC

*S14 Indoor Only
**Note: Available only in 4 filament
***MOQ - Consult Factory

Specification

2 Filament (based on Clear 2200K)				
Lumens (lm/fixture)	80	105	105	105
CRI	>80			
Efficacy (lm/W)	80	105	52.5	52.5
Beam Angle	360°			
Power Consumption (W/Blub)	1W	1W	2W	2W
4 Filament (based on Clear 2700K)				
Lumens (lm/fixture)	N/A	N/A	CF	N/A
CRI	>80			
Efficacy (lm/W)	N/A	N/A	CF	N/A
Beam Angle	360°			
Power Consumption (W/Blub)	N/A	N/A	3W	N/A
Control				
Dimming	NO	YES	YES	YES
Electrical				
Input Voltage	120V AC			
Physical				
Bulb	Vacuum Sealed			
Base	Nickle Coated Brass Base			
Certification and Testing				
Certification	ETL			
IP Rating (PC/PET Bulb)	IP54, Indoor Location			
Rated Life	30,000 hrs.			
Warranty	5 years			

Tivoli, LLC. reserves the right to modify this specification without prior notice.