Project: _____ TYPE: _____

- Low bin tolerance with a 2 Step McAdam Elipse standard
- Outdoor location suited with Tivoli's eXo Shield coating
- High CRI value
- Factory soldered lead wire required
- IP54 damp location available
- Multiple mounting channel options
- Large range of available Kelvin temperatures
- Low lead times
- 5 Year warranty

Dimensions

Tivoli, LLC. reserves the right to modify this specification without prior notice.
Copyright © 2021 Tivoli 09.04.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Order Guide

PRODUCT CODE		INTENSITY		INSTALL		LED COLOR		VOLTAGE
TPLD	-	**SB**	-	**O**	-		-	**24**
TPLD = Tivotape DEFINE		**SB** = Standard Brightness		**O** = Outdoor		**22** = 2200°K **24** = 2400°K **27** = 2700°K **30** = 3000°K **35** = 3500°K **40** = 4000°K **50** = 5000°K		**24** = 24V DC

Specification

Output (based on 3000K)							
Kelvin Temperature	2200K	2400K	2700K	3000K	3500K	4000K	5000K
Lumens/ft	164	168	205	210	214	216	220
Efficacy (Lm/W)	65	69	72	73	75	78	79
Color Rendering Index (CRI)	90+						
Electrical							
Input Voltage	24V DC						
Power Supply	Class 2						
Power Consumption W/ft	3 W/ft.						
Max Mechanical Run	15'						
Max Electrical Run	32'						
Wire Size (End Prep)	18 AWG, 2 wire						
Dimming	MLV/ELV/0-10V (Consult factory for DMX dimming)						
Physical							
LED Package	3528						
LEDs/ft	36						
Adhesive	3M VHB Tape						
Copper Trace	3 Ounce						
Dimensions	0.4375" (11.11mm) Jacket						
Cut Increments	2" (non-field cuttable - Factory prep only)						
Operating Temperature	-40°F (-40°C) ~ 140°F (60°C)						
Certification and Testing							
Certification	cULus Listed						
Lumen Maintenance (L70) Hours	60,000						
Binning Tolerance	2 Step MacAdam Elipse						
Environment	IP67 Wet Location, Conformally Coated						
Warranty	5 Years						

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 09.04.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Power Leads and Jumpers (Installed by Tivoli's certified solderers)



TPL-O-LEAD-2-C
LEAD/END
24" standard 2 conductor 18AWG lead wire factory attached to one end of tape



TPL-O-LEAD-2-D
LEAD/LEAD
24" standard 2 conductor 18AWG lead wire factory attached to both ends of tape

TPL-O-XEP-2
EXTRA LEAD WIRE
Additional factory attached 18AWG lead 2 wire to extend lengths of LEAD-C and LEAD-D up to 20 ft. max
Sold per foot



TPL-O-CONN
18-22AWG BUTT CONNECTORS
Used to interconnect factory attached lead wires.
Sold individually.

GELJB-3-01-BK
1/2/3 Wire IP67 Small Gel Filled Junction Box

GELJB-3-02-BK
1/2/3 Wire IP67 Medium Gel Filled Junction Box

Compatible Extrusions



MCHAN-8-LP
Low profile NO LENS OPTION clear polycarbonate, length 8'



TPL-I-45-MCH-8-S
White PVC, 45° NO LENS length 8'



DWAR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5' lengths



EDGE-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5' lengths



COTA-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5' lengths



MOFT-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5' lengths



DYER-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5' lengths



WRNR-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5' lengths

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 09.04.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Compatible Extrusions



NOYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



VALN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



DOME-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



ALTN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



MRSL-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



HRIZ-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



ASTR-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length



EDIN-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



FRE-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



RIDG-CHAN-SLV-8
Anodized Aluminum Extrusion length 8′



DUET-04-CHAN-XXX-6.5
XXX = **SLV** (silver), **WHT** (white), **GLD** (gold), **BLK** (black)
Aluminum extrusion
6.5′ Length



DUET-04-CHAN-SLV-6.5
Anodized aluminum extrusion available in 6.5′ length

Note: **DUET-04-CHAN-SLV-6.5** and **DUET-04-LNS-R-XXX-6.5** are required for recessed application



DUET-04-CHAN-M-6.5
Mud-In PC fire-proof extrusion
6.5′ Length

Note: **DUET-04-CHAN-SLV-6.5** and **DUET-04-CHAN-M-6.5** are required for mud-in application



CARU-CHAN-SLV-6.5
Anodized aluminum extrusion, available in 6.5′ lengths



HAYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion, available in 6.5′ lengths



ANZI-CHAN-XXX-6.5
XXX=SLV (Silver), **BLK** (Black), **WHT** (White)
Anodized Aluminum Extrusion, available in 6.5′ lengths

Note: For complete information on DUET 04 profile, refer to specification

Tivoli, LLC. reserves the right to modify this specification without prior notice.

In-Wall Controls

Touchscreen

TVOQ-1-WH
White

Touchscreen

TVOQ-10-XX-7
XX = **BK** (Black), **WH** (White)

Touchscreen

TVOQ-2-BK
Black

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Recommended Power Supplies

ADNM - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-D	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-D				1	96W	4A
	ADNM-240-2-4-24-D				2	2x96W	2x4A
	ADNM-320-3-4-24-D				3	3x96W	3x4A

ADNM - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DOT	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-DOT				1	96W	4A
	ADNM-240-2-4-24-DOT				2	2x96W	2x4A
	ADNM-320-3-4-24-DOT				3	3x96W	3x4A

ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DIN	Indoor / Outdoor	100-277V AC 5o/60 Hz	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-DIN				1	96W	4A
	ADNM-240-2-4-24-DIN				2	2x96W	2x4A
	ADNM-320-3-4-24-DIN				3	3x96W	3x4A

ADNM - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-240-2-4-24-DIN-2	Indoor / Outdoor	100-277V AC 5o/60 Hz	24V DC	2	2x96W	2x4A
	ADNM-320-3-4-24-DIN-3				3	3x96W	3x4A

ADNM - DMX/DALI FLICKER-FREE FOR TV STUDIO

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-120-1-4-24-DTV	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	1x96W	1x4A
	ADNM-240-2-4-24-DTV				2	2x96W	2x4A
	ADNM-320-3-4-24-DTV				3	3x96W	3x4A

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 09.04.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458

Recommended Power Supplies

INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-1.3-24	Indoor / Outdoor	100 - 277V AC	24V DC	1	30W	3W	1.3A
	INF-J-60-1-2.5-24				1	60W	6W	2.5A
	INF-J-96-1-4-24				1	96W	9W	4A
	INF-J-192-2-4-24				2	2x96W	2x9W	2x4A
	INF-J-288-3-4-24				3	3x96W	3X9W	3x4A

Recommended Dimmers

DIMMING - 0-10V

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD	PRICE
0-10V Dimmer	DIM-LD-010	Indoor	12V/24V DC	12V/24V DC	30 mA max. output (sink only)	$ 120.00/ea

DIMMING -MLV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
MLV Dimmer	N-600	Indoor	120V AC	120V AC	450W
	N-1000				800W
	N-1500				1200W
	D-600				450W
	M-600				450W
	M-1000				800W

DIMMING - ELV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
ELV Dimmer	ME-600	Indoor	120V AC	120V AC	450W
	DE-300				300W

Tivoli, LLC. reserves the right to modify this specification without prior notice.

Copyright © 2021 Tivoli 09.04.2026

www.tivolilighting.com tel: 714-957-6101 fax: 714-427-3458