



Project: _____ Type: _____

- Tunable white from 2200K - 6000K range for precise color choice when used with DMX controls and software
- Factory molded power lead and end cap
- Constructed using flexible SMD LEDs with zero voltage drop for reliability and uniformity of light
- Used to outline structures or where traditional glass neon is used
- Low Voltage 24V DC
- Long-life LEDs with tight cutting increments for precise field installation
- UV Stabilized for exterior use with silicone housing (no yellowing or cracking)
- IP67 Rating
- IK07 Rating - protected against 2 joules impact



Dimensions





Order Specification Guide

NOTE: Lengths and quantity of each run must be submitted at time of order.
TRACE is factory prep only. In-field cutting will void warranty.


PRODUCT CODE	INTENSITY	PROFILE	LED COLOR	RANGE	VOLTAGE
TRCE		V	TW	01	24
TRCE = Trace Flexible Light	L = Low Output S = Standard Output H = High Output	V = Vertical	TW = Tunable White	01 = 2200-6000K	24 = 24V DC

Specifications


LED Intensity	Low Output	Standard Output	High Output
Lumens (lm/ft)	73	149	204
Beam Angle	115.8°		
LEDs	3014		
Electrical			
Dimming	DMX		
Input Voltage	24V DC		
Power Consumption (W/ft)	1.5	3	4.5
Maximum Run	58'	29'	19'
Physical			
Dimensions	5/8" X 19/32"		
Cutting Increments	1.97"		
Material	UV, Solvent, Saltwater resistant silicone		
Wire Exit Options	Front, Side, Bottom		
LED PIN Temperature	60.9°C / 141.6°F		
Storage Temperature	-25°C / -13°F - 60°C / 140°F		
Ambient Temperature	Ta _{min} = -25°C / -13°F, Ta _{max}		
Certification and Testing			
Certification	cULus		
Rated Life L70/hrs	54,000		
Environment	Wet Location		
IP Rating	IP67		
IK Rating	IK07		
Warranty	3 Years		

- Maximum Run length refers to single side feed in serial connection
- The given color temperature is the strip (after coating) color temperature
- The given data are typical values due to the tolerances of the production process and electrical components; values for the light output and electrical power can vary up to 10%


Factory Molded Power Lead and End Caps




FRONT
Vertical Front Lead Entry
10' Power Lead Cable with End Cap



SIDE
Vertical Side Lead Entry
10' Power Lead Cable with End Cap



BOTTOM
Vertical Bottom Lead Entry
10' Power Lead Cable with End Cap




END CAP
Vertical End Cap (No Lead)


Power Leads - How to Configure

It is important to note the orientation of TRACE TW and what is considered Left Facing and Right Facing. TRACE TW is polarity specific and proper submission of power leads for each run is necessary for factory prep standards.


VERTICAL TRACE TW - The cut window will always indicate as Bottom (Image B) and positive (+) polarity will indicate front facing (Image A).




Molded Power Lead Configurations



TRCE-V-TW-MLEAD-B-B
Left Facing Bottom Lead with 10' Power Cable to
Right Facing Bottom Lead with 10' Power Cable




TRCE-V-TW-MLEAD-F-F
Left Facing Front Lead with 10' Power Cable to
Right Facing Front Lead with 10' Power Cable




TRCE-V-TW-MLEAD-S-S
Left Facing Side Lead with 10' Power Cable to
Right Facing Side Lead with 10' Power Cable


Molded Power Lead Configurations




TRCE-V-TW-MLEAD-B-F
 Left Facing Bottom Lead with 10' Power Cable to Right Facing Front Lead with 10' Power Cable




TRCE-V-TW-MLEAD-F-B
 Left Facing Front Lead with 10' Power Cable to Right Facing Bottom Lead with 10' Power Cable




TRCE-V-TW-MLEAD-S-F
 Left Facing Side Lead with 10' Power Cable to Right Facing Front Lead with 10' Power Cable



TRCE-V-TW-MLEAD-F-S
 Left Facing Front Lead with 10' Power Cable to Right Facing Side Lead with 10' Power Cable




TRCE-V-TW-MLEAD-B-S
 Left Facing Bottom Lead with 10' Power Cable to Right Facing Side Lead with 10' Power Cable




TRCE-V-TW-MLEAD-S-B
 Left Facing Side Lead with 10' Power Cable to Right Facing Bottom Lead with 10' Power Cable


Molded Power Lead Configurations




TRCE-V-TW-MLEAD-E-B
Left End Cap Lead to Right Facing Bottom Lead with 10' Power Cable




TRCE-V-TW-MLEAD-B-E
Left Facing Bottom Lead with 10' Power Cable to Right End Cap




TRCE-V-TW-MLEAD-E-F
Left End Cap Lead to Right Facing Front Lead with 10' Power Cable



TRCE-V-TW-MLEAD-F-E
Left Facing Front Lead with 10' Power Cable to Right End Cap




TRCE-V-TW-MLEAD-E-S
Left Facing End Cap Lead to Right Facing Side Lead with 10' Power Cable




TRCE-V-TW-MLEAD-S-E
Left Facing Side Lead with 10' Power Cable to Right Facing End Cap


Mounting Options



TRCE-V-SLS-MTCLIPS
Mounting Clips Vertical Profile 2
Stainless Steel Clips with 2 Screws



TRCE-V-SLV-SCHAN-6.5
Straight Channel Vertical Profile
6.56' Length, Aluminum



TRCE-V-SLV-NCHAN-6.5
Notched Channel Vertical Profile
Radius Bend: 11"
6.56' Length, Aluminum



FLXD-SIL-GE-10
GE Silicone 10oz Tube
Use to adhere TRACE into entire
run length of channel
10oz tube/25' bead length

In-Wall Controls



TVOQ-10-XX-7
XX = BK (black), WH (white)
1024 DMX channel, 500 scene,
10 zone, glass touch screen



TVOQ-2-BK
Black, 512 DMX channel, 99 scene,
1 zone, glass touch screen



TVOQ-1-WHT
512 DMX channel, 16 scene,
4 zone, glass touch screen



Power Supplies - Indoor

ADUL - VARIABLE / DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-120-1-4-24-VW	Indoor / Damp	100-277V AC 50/60 HZ	24V DC	1	96W	4A
	ADUL-240-2-4-24-VW				2	2x96W	2x4A
	ADUL-320-3-4-24-VW				3	3x96W	3x4A

ADUL - VARIABLE / DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-240-2-4-24-VW-2	Indoor / Damp	100-277V AC 50/60 Hz	24V DC	2	2x96W	2x4A
	ADUL-320-3-4-24-VW-3				3	3x96W	3x4A

Power Supplies - Outdoor

ADNM - VARIABLE / DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-VW	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-VW				1	96W	4A
	ADNM-240-2-4-24-VW				2	2x96W	2x4A
	ADNM-320-3-4-24-VW				3	3x96W	3x4A

ADNM - VARIABLE / DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-240-2-4-24-VW-2	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	2	2x96W	2x4A
	ADNM-320-3-4-24-VW-3				3	3x96W	3x4A

DMX Sub-Controller

DESCRIPTION	CAT NO	MODES	WATTAGE	PRIMARY VOLTAGE	DIMENSION
DMX Basic Subcontroller	TPL-RGBW-180-24	Subcontroller only	5X96W	24V DC	2.87" W X 6.46" L X 1.45" H