

**tivoli**



**LITESPHERE**  
**ADAPT DROP**

## ADAPT Drop String Light- How it works

A simple 3 step order process for cord spacing, drop length with light engine and globe choice for endless design combinations to create a unique experience for personal or public space.

### ● CONNECTION

IP65 Outdoor 2 pin twist connector for solid, reliable performance.

### ● SHADE ADAPTER - optional

Tivoli's Patent Pending universal shade adapter allows you to mix and match any shade with our line of String Light.

### ● LIGHT SHADE - optional

Multiple light shades to choose from to add form and function to your design.

### ● DROP

Tivoli's New DROP system gives you standard 3 length options and a custom offering for additional lengths.

### ● VHO LED

With 90 lumens each, Tivoli's VHO wedge based LED is 23 times brighter than our standard output offering. Built with Nichia SMD LEDs and a thermal plastic base for optimal heat dissipation.

### ● ADAPT GLOBES & ADAPTER

11 globe options to finish your design and achieve a personal look.



# 1 Choose Your Cord

\*Max run lengths based on Tivoli's recommended lumen drop.  
 \*\*Weights are based on (1) 50' single run ONLY - no globe or drop attached.

## Order Information

### LSD-STRND-24

BLACK, 24" OC, strand only (no DROP)  
 includes push PVC end cap for field cutting.



**NOTE:** (1) LSD-LEAD-10 must be ordered with each, complete electrical maximum run.

ON CENTER SPACING	*MAX ELECTRICAL RUN	WATT PER FOOT	**WEIGHT (50' STRAND ONLY)
24"	50'	0.48	3.56 lbs.




## Order Information

### LSD-STRND-36

BLACK, 36" OC, strand only (no DROP)  
 includes push PVC end cap for field cutting.

ON CENTER SPACING	*MAX ELECTRICAL RUN	WATT PER FOOT	**WEIGHT (50' STRAND ONLY)
36"	100'	0.32	3.89 lbs.



## Order Information


### LSD-STRND-48

BLACK, 24" OC strand - Staggered socket capped spacing to 48" OC, strand only (no DROP)  
 includes push PVC end cap for field cutting.

ON CENTER SPACING	*MAX ELECTRICAL RUN	WATT PER FOOT	**WEIGHT (50' STRAND ONLY)
48"	120'	0.24	3.56 lbs.



## 2 Choose Your DROP Option & LED Color



### Order Information

#### **LSAD-DRP-XX-12**

BLACK, 12" ADAPT DROP

#### **LSAD-DRP-XX-24**

BLACK, 24" ADAPT DROP

#### **LSAD-DRP-XX-36**

BLACK, 36" ADAPT DROP

**XX** = Kelvin Temperature Option: 19, 27, 30, 35, 40, 50, AM, RD, GN, YL, RB

### TOTAL WEIGHT

12": 0.15 lbs.

24": 0.19 lbs.

36": 0.22 lbs.

All DROPS are pre-built with Adapter and VHO LED chip and ready to install in field.

\* Consult factory for lead time and MOQ



### 3 Choose Your Globe

**LSA Globes:** All ADAPT globes come with (1) foam washer each.



Shatter Resistant Silicone Coating  
(Shatter resistance assist with silicone coating - Glass may still break under certain conditions)

G125 Globe (Weight: 4 oz./ea.)



Ana  
**LSA-ANA**



Angela  
**LSA-ANG**



Gina  
**LSA-GIN**



Gaby  
**LSA-GAB**



Katie  
**LSA-KAT**



Susan\*  
**LSA-SUS**



Toni\*  
**LSA-TON**



Lucia\*  
**LSA-LUC**



Victoria\*  
**LSA-VIC**

\*Consult Factory for MOQ and Lead Time.

ST19 Globe (Weight: 1.6 oz./ea.)



Laura\*  
**LSA-LAU**




Shatter Resistant  
Silicone Coating




Brenda  
**LSA-BRE**

## Light Shades

### HAT




**SHADE-HT-BK-BK-8**  
Light Shade - HAT  
8.3" Black Top, Black Bottom



**SHADE-HT-BK-BK-13**  
Light Shade - HAT  
12.6" Black Top, Black Bottom  
**\*SHADE-HT-BK-CO-13**  
Light Shade - HAT  
12.6" Black Top, Copper Bottom



\*Consult factory for lead time and MOQ

### DISH




**SHADE-DS-BK-BK-10**  
Light Shade - DISH  
10.2" Black Top, Black Bottom

### FLOWER



**SHADE-FL-BK-BK-10**  
Light Shade - FLOWER  
9.8" Light Shade, Black Top, Black Bottom



**SHADE-FL-BK-BK-13**  
Light Shade - FLOWER  
13.8" Light Shade, Black Top, Black Bottom

### Accessories

#### SHADE-ADP-BK-01 Light Shade Adapter - Single

PVC Black Adapter - Sold individually. Includes (1) Adapter, (1) Adapter plates, (2) set screws and (1) Allen Key

#### SHADE-ADP-BK-26 Light Shade Adapter - 24" OC

PVC Black Adapter Kit - Sold in packs of 26. Includes (26) Adapters, (26) Adapter plates, (52) set screws and (1) Allen Key

#### SHADE-ADP-BK-17 Light Shade Adapter - 36" OC

PVC Black Adapter Kit - Sold in packs of 17. Includes (17) Adapters, (17) Adapter plates, (34) set screws and (1) Allen Key

#### SHADE-ADP-BK-13 Light Shade Adapter - 48" OC

PVC Black Adapter Kit - Sold in packs of 13. Includes (13) Adapters, (13) Adapter plates, (26) set screws and (1) Allen Key



Shade Adapter Assembly Example

## Mounting

Multi-purpose cable with cable locks for quick, reliable support up to 330 pounds of load and spans from 60 - 500 feet.

**WARNING:** For suspension application, catenary cable is required to support the product, otherwise the warranty will be void.



**LS-CABLE-60** Catenary Cable Kit - 60'  
(1/8" galvanized aircraft cable includes 2 cables locks for use with loads up to 200lbs)

**LS-CABLE-110** Catenary Cable Kit - 110'  
(1/8" galvanized aircraft cable includes 2 cables locks for use with loads up to 200lbs)

**LS-CABLE-500** Catenary Cable Kit - 500'  
(1/8" galvanized aircraft cable for use with loads up to 200lbs)



**LS-LOCK-X** Cable Lock  
X = 2 (2 Locks), 4 (4 locks) Includes (1) cable release key.  
Cable Lock for 1/8th inch cable, Heavy-duty lockable fasteners support loads up to 200 lbs. Can be easily adjusted without the use of tools.



**LS-TT** Catenary Tensioning Tool  
Catenary Cable Tensioning Tool up to 880lbs with minimal effort due to the 6:1 gear drive mechanism. Integral torque gauge controls the load applied to the wire, giving consistent tension every time and optimizing the life of the wire.




**LS-UVZP-BK-50** UV Zip Ties  
50 pc Bag set. UV resistant, heavy duty ties.  
Maximum weight up to 100 lbs./per tie.






**LS-UVZP-BK-30** UV Zip Ties  
30 pc Bag set. UV resistant, heavy duty ties.  
Maximum weight up to 100 lbs./per tie.


## Installation with Suspension Cable



## Replacement Parts


Light Engine	Lead Wire	End Cap
 <p><b>LSL-19-V-12</b> 12V Wedge base 1900K</p> <p><b>LSL-27-V-12</b> 12V Wedge base 2700K</p> <p><b>LSL-30-V-12</b> 12V Wedge base 3000K</p> <p><b>LSL-35-V-12</b> 12V Wedge base 3500K</p> <p><b>LSL-40-V-12</b> 12V Wedge base 4000K</p> <p><b>LSL-50-V-12</b> 12V Wedge base 5000K</p> <p><b>LSL-AM-V-12</b> 12V Wedge base Amber</p> <p><b>LSL-RD-V-12</b> 12V Wedge base Red</p> <p><b>LSL-RB-V-12</b> 12V Wedge base Royal Blue</p> <p><b>LSL-GN-V-12</b> 12V Wedge base Green</p> <p><b>LSL-YL-V-12</b> 12V Wedge base Yellow</p>	 <p><b>LSD-LEAD-10</b> 10' Lead Wire IP67 Female Twist Connection to SJTW 16AWG/2C bare wire.</p>	 <p><b>LSD-EC-PK20</b> BLACK, T-Socket End Cap, PVC - sold in packs of 20</p>

## DMX In-Wall Controls




### TVOQ-1-WH

White  
16 DMX channel, 16 scene,  
4 zone, glass touch screen



### TVOQ-10-XX-7

XX = BK (Black), WH (White)  
1024 DMX channel, 500 scene,  
10 zone, glass touch screen



### TVOQ-2-BK

Black  
512 DMX channel, 99 scene,  
1 zone, glass touch screen



## Recommended Power Supplies

### ADNM - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-60-1-5-12-D	Indoor / Outdoor	100-277V AC 50/60 HZ	12V DC	1	60W	5A
	ADNM-80-1-5-12-D				1	60W	5A
	ADNM-150-2-5-12-D				2	2x60W	2x5A
	ADNM-240-3-5-12-D				3	3x60W	3x5A
	ADNM-320-4-5-12-D				4	4x60W	4x5A

### ADNM - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-60-1-5-12-DOT	Indoor / Outdoor	100-277V AC 50/60 HZ	12V DC	1	60W	5A
	ADNM-80-1-5-12-DOT				1	60W	5A
	ADNM-150-2-5-12-DOT				2	2x60W	2x5A
	ADNM-240-3-5-12-DOT				3	3x60W	3x5A
	ADNM-320-4-5-12-DOT				4	4x60W	4x5A

### ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-60-1-5-12-DIN	Indoor / Outdoor	100-277V AC 50/60 HZ	12V DC	1	60W	5A
	ADNM-80-1-5-12-DIN				1	60W	5A
	ADNM-150-2-5-12-DIN				2	2x60W	2x5A
	ADNM-240-3-5-12-DIN				3	3x60W	3x5A
	ADNM-320-4-5-12-DIN				4	4x60W	4x5A

### ADNM - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-150-2-5-12-DIN-2	Indoor / Damp	100-277V AC 50/60 Hz	12V DC	2	2x60W	5A
	ADNM-240-3-5-12-din-3				3	3x60W	3x5A

### INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

Dim to 1% with a 0-10V Lutron Diva dimmer (by others)

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-2.5-12	Indoor / Outdoor	100 - 277V AC	12V DC	1	30W	3W	2.5A
	INF-J-60-1-5-12				1	60W	6W	5A
	INF-J-180-3-5-12				3	3x60W	3x6W	3x5A
	INF-J-300-5-5-12				5	5x60W	5x6W	5x5A