



Project: _____ TYPE: _____

- Riveted Wire Guard meets NEC #520.72 standard
- Heavy-gauge extruded aluminum
- Available in 6", 9", 12" and 18" OC standard spacing
- Wiring and components are concealed
- Anti-corrosion coated (Custom Finished on Request)
- Custom radial bends
- 2.188" x 2.188" Standard Profile extrusion available
- Optional 4 Channel chase wiring is available
- Configurable for freight optimization
- Pre-wired for quick and easy installation
- Knock-out holes for screws are provided every 24"
- 7/8" diameter knockouts on mounting side (custom optional end cap knockouts)

Dimensions





Order Guide

AC Standard Architectural Channel maximum length 12'


PRODUCT CODE	SOCKET TYPE	LAMP SPACING	FINISH	OPTIONAL CHASSING
AC	WB			
AC = Standard	WB = Wire Guard Base	06 = 6" OC 09 = 9" OC 12 = 12" OC 18 = 18" OC 24 = 24" OC	SA = Satin Aluminum BK = Black Powder Coat WH = White Powder Coat	CC1 = 120V 4 Channel Chasing CC2 = 220/240V 4 Channel Chasing

Specification


Electrical	
Operating Voltage	120V AC/ 240V AC
Physical	
Dimensions	AC Standard 2.188" W x 2.188" H (without bulb)
Socket Spacing*	6", 9", 12", 18" and 24" OC
Order increments	1' (12' max)
Housing	Aluminum
American Wire Gauge	20 AWG
Mounting	Surface Mount, Suspended
Knock-out Holes	Every 24" along mounting face of channel
Sockets	Medium Base, E26/E27
Lamps (By others)	60W max
Certification and Testing	
Certification	cULus
Environment	Dry Location
IP Rating	IP54
Warranty	5 Years

*Custom lamp spacing available (consult factory)
 **Custom paint or anodizing available (consult factory)


Compatible Tivolite




TVLT-A19-X-X-26-XX-120
X (Filament Count) = 1, 2, 6
X = F (Frosted), V (Vintage),
C (Clear)
XX (CCT) = 22, 24, 27
 A19 Tivolite Bulb




TVLT-S14-X-X-26-XX-120
X (Filament Count) = 1, 2, 4, 6
X = F (Frosted), V (Vintage),
C (Clear)
XX (CCT) = 22, 24, 27
 S14 Tivolite Bulb




TVLTPET-G125-4-C-26-XX-120
XX (CCT) = 24, 27
 G125 PET Tivolite Bulb



L19-6.5-A19-V-24-D
 A19 Tivolite Vintage Standard Bulb
 2400K



L19-6.5-A19-F-27-D
 A19 Tivolite Vintage Frosted Bulb
 2700K




L19-6.5-G25-V-24-D
 G25 Tivolite Vintage Bulb
 2400K




L19-6.5-ST19-V-24-D
 ST19 Tivolite Vintage Bulb
 2400K


Accessories and Joiners




AC-90
 Flat 90° (Standard)
 Internal 90° Bracket




AC-45
 45° Bracket (Standard)
 Internal 45° Bracket




AC-T
 T Bracket (Standard)
 internal T-bracket




AC-180
 Internal Connector (Standard)




AC-EC-XX
XX = SA (Satin Aluminum),
PW (Powder Coated White),
PB (Powder Coated Black)
 Standard Profile End Caps



AC-90-OI
 90° (Standard Outside/Inside)
 Internal 90° Bracket




CC4-120V
 120V 1-4 Channel
 Chase Controller with
 adjustable chase speed rate of
 1-30 step per/sec.




CC4-220V
 220V-240V 1-4 Channel
 Chase Controller with
 adjustable chase speed rate of
 1-30 step per/sec.


Channel Configurations




RADIUS
Radius bend set up charge
(Over 3' Radius)
Note: Indicate lamp position at
time of ordering




RADIUS-3
Radius bend set up charge
(Under 3' Radius)
Note: Indicate lamp position at
time of ordering



R-UNITS
Radius unit charge, Per 8' Max
length
Note: Indicate lamp position
at time of ordering



AC-RADIUS
Internal Bracket



AC-MITER
Factory Miter Cut