


TRACE

 RGB Vertical





Project: _____ Type: _____

Product Features

- Red, Green and Blue mixing for precise color choice when used with DMX controls and software
- Constructed using flexible SMD LEDs with zero voltage drop for reliability and uniformity of light
- Used to outline structures or where traditional glass neon is used
- Low Voltage 24V DC
- Long-life LEDs with tight cutting increments for precise field installation
- UV Stabilized for exterior use with silicone housing (no yellowing or cracking)
- IP67 Rating
- IK07 Rating - protected against 2 joules impact



Dimensions



Order Specification Guide

NOTE: Lengths and quantity of each run must be submitted at time of order.
 TRACE is factory prep only. In-field cutting will void warranty.

PRODUCT CODE	INTENSITY	PROFILE	LED COLOR	VOLTAGE
TRCE		V	RGB	24
TRCE = Trace Flexible Light	L = Low Output S = Standard Output H = High Output	V = Vertical	RGB = Red, Green, Blue	24 = 24V DC


Specifications

Output (2700K)			
LED Intensity	Low Output	Standard Output	High Output
Lumens (lm/ft) All On	39	65	91
Beam Angle	115.8°		
LEDs	4040		
Electrical			
Dimming	DMX		
Input Voltage	24V DC		
Power Consumption (W/ft)	1.5	3	4.5
Maximum Run	58'	29'	19'
Physical			
Dimensions	5/8" X 19/32"		
Cutting Increments	2.46"		
Material	UV, Solvent, Saltwater resistant silicone		
Wire Exit Options	Front, Side, Bottom		
LED PIN Temperature	60.9°C / 141.6°F		
Storage Temperature	-25°C / -13°F - 60°C / 140°F		
Ambient Temperature	Ta _{min} = -25°C / -13°F, Ta _{max}		
Certification and Testing			
Certification	cULus		
Environment	Wet Location		
IP Rating	IP67		
Warranty	3 Years		


- Maximum Run length refers to single side feed in serial connection
- The given color temperature is the strip (after coating) color temperature
- The given data are typical values due to the tolerances of the production process and electrical components; values for the light output and electrical power can vary up to 10%

Power Lead Options - Vertical


IP67: Rated for outdoor use and factory assembled.
 Note: The end cap is made of UV stabilized polycarbonate, which produces no yellowing and cracking over time.




TRACE RGB LEAD - FRONT
 Vertical Front Lead Entry
 5' Power Lead Cable with End Cap




TRACE RGB LEAD - SIDE
 Vertical Side Lead Entry
 5' Power Lead Cable with End Cap



TRACE RGB LEAD - BOTTOM
 Vertical Bottom Lead Entry
 5' Power Lead Cable with End Cap




TRACE END CAP
 Vertical End Cap (No Lead)
 1 pc End Cap with 4 Screws




Power Leads - How to Configure

It is important to note the orientation of TRACE RGB and what is considered Left Facing and Right Facing. TRACE RGB is polarity specific and proper submission of power leads for each run is necessary for factory prep standards.


VERTICAL TRACE RGB - The cut window will always indicate as Bottom (Image B) and positive (+) polarity will indicate front facing (Image A).




Power Lead Configurations - RGB



TRCE-V-RGB-LEAD-B-B
Left Facing Bottom Lead with 5' Power Cable to
Right Facing Bottom Lead with 5' Power Cable




TRCE-V-RGB-LEAD-F-F
Left Facing Front Lead with 5' Power Cable to
Right Facing Front Lead with 5' Power Cable




TRCE-V-RGB-LEAD-S-S
Left Facing Side Lead with 5' Power Cable to
Right Facing Side Lead with 5' Power Cable


Power Lead Configurations - RGB




TRCE-V-RGB-LEAD-B-F
 Left Facing Bottom Lead with 5' Power Cable to
 Right Facing Front Lead with 5' Power Cable




TRCE-V-RGB-LEAD-F-B
 Left Facing Front Lead with 5' Power Cable to
 Right Facing Bottom Lead with 5' Power Cable




TRCE-V-RGB-LEAD-S-F
 Left Facing Side Lead with 5' Power Cable to
 Right Facing Front Lead with 5' Power Cable



TRCE-V-RGB-LEAD-F-S
 Left Facing Front Lead with 5' Power Cable to
 Right Facing Side Lead with 5' Power Cable




TRCE-V-RGB-LEAD-B-S
 Left Facing Bottom Lead with 5' Power Cable to
 Right Facing Side Lead with 5' Power Cable




TRCE-V-RGB-LEAD-S-B
 Left Facing Side Lead with 5' Power Cable to
 Right Facing Bottom Lead with 5' Power Cable


Power Lead Configurations - RGB




TRCE-V-RGB-LEAD-E-B
Left End Cap Lead to Right Facing Bottom Lead with 5' Power Cable




TRCE-V-RGB-LEAD-B-E
Left Facing Bottom Lead with 5' Power Cable to Right End Cap




TRCE-V-RGB-LEAD-E-F
Left End Cap Lead to Right Facing Front Lead with 5' Power Cable



TRCE-V-RGB-LEAD-F-E
Left Facing Front Lead with 5' Power Cable to Right End Cap



TRCE-V-RGB-LEAD-E-S
Left Facing End Cap Lead to Right Facing Side Lead with 5' Power Cable





TRCE-V-RGB-LEAD-S-E
Left Facing Side Lead with 5' Power Cable to Right Facing End Cap



Accessories




TRCE-V-SLV-SCHAN-6.5
 Straight Channel
 Vertical Profile Only
 6.56' Length, Aluminum



TRCE-V-SLV-NCHAN-6.5
 Notched Channel
 Vertical Profile Only
 Radius Bend: 11"
 6.56' Length, Aluminum



TRCE-V-SLS-MTCLIPS
 Mounting Clips
 Vertical Profile Only
 2 Stainless Steel Clips with 2 Screws



FLXD-SIL-GE-10
 GE Silicone Tube
 Use to adhere TRACE into entire run length of channel
 25' estimated bead length per 10oz tube



DMX-SPLT-8
 DMX Splitter
 8 ports of DMX 512, RJ45 and 3-pin Hardwire Connection

Note: If the number of DMX sub-controllers exceed 32 units, a DMX Splitter is required.

Controls & Software


CONTROLS



Touchscreen

TVOQ-10-XX-7

XX = BK (black), WH (white)
1024 DMX channel, 500 scene,
10 zone, glass touch screen



Touchscreen

TVOQ-2-XX

XX = BK (black), WH (white)
512 DMX channel, 99 scene,
1 zone, glass touch screen



Touchscreen

TVOQ-1-WHT

512 DMX channel, 16 scene,
4 zone, glass touch screen

SOFTWARE



Cue™ and CuePro™ softwares are specifically designed for the TivoCUE™ in-wall DMX controls and includes an array of tools required by the latest DMX lighting fixtures. Intuitive, with easy-to-use effects that can be dropped into timelines, and multi-zone synchronization capabilities allow you to program a project effortlessly.



Power Supplies - Indoor
ADUL - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-120-1-4-24-DIN	Indoor / Damp	100-277V AC 5ø60 Hz	24V DC	1	96W	4A
	ADUL-240-2-4-24-DIN				2	2x96W	2x4A
	ADUL-320-3-4-24-DIN				3	3x96W	3x4A

ADUL - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-240-2-4-24-DIN-2	Indoor / Damp	100-277V AC 5ø60 Hz	24V DC	2	2x96W	2x4A
	ADUL-320-3-4-24-DIN-3				3	3x96W	3x4A

Power Supplies - Outdoor
ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DIN	Indoor / Outdoor	100-277V AC 5ø60 Hz	24V DC	1	90W	3.75A
	ADNM-120-1-4-24-DIN				1	96W	4A
	ADNM-240-2-4-24-DIN				2	2x96W	2x4A
	ADNM-320-3-4-24-DIN				3	3x96W	3x4A

ADNM - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-240-2-4-24-DIN-2	Indoor / Outdoor	100-277V AC 5ø60 Hz	24V DC	2	2x96W	2x4A
	ADNM-320-3-4-24-DIN-3				3	3x96W	3x4A

ADNM - DMX/DALI FLICKER-FREE FOR TV STUDIO RGB/RGBW

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-120-1-4-24-DTVC	Indoor / Outdoor	100-277V AC 5ø60 Hz	24V DC	1	1x96W	1x4A
	ADNM-240-2-4-24-DTVC				2	2x96W	2x4A
	ADNM-320-3-4-24-DTVC				3	3x96W	3x4A

DMX Sub-Controller

DESCRIPTION	CAT NO	MODES	WATTAGE	PRIMARY VOLTAGE	DIMENSION
DMX Sub-controller	TPL-RGBW-180-24	Sub-controller only	5X96W	24V DC	2.87" W X 6.46" L X 1.45" H